

AM308

Indoor Ambience Monitoring Sensor
Featuring LoRaWAN®



◆ Introduction

AM30x is a compact indoor ambience monitoring sensor for measurement of temperature, humidity, light, CO2 concentration, TVOC, barometric pressure, PM2.5, PM10 and motion. The data will be shown on the E-ink screen in real-time, which helps to measure the indoor environment and comfort. AM30x is widely used for offices, stores, classrooms, hospitals, etc.

Sensor data is transmitted using LoRaWAN® technology. Combining Milesight LoRaWAN® gateway and Milesight IoT Cloud, users can manage all sensor data remotely and visually.

◆ Features

- Integrated with multiple sensors like humidity, temperature, CO2, light, barometric pressure, PM2.5, PM10, etc.
- Multiple display modes and clear emoticon to easily understand the comfort levels via screen
- Support batteries or DC power supply
- Equipped with traffic light indicator and buzzer to indicate device status and threshold alarms
- Store locally 18,000 historical records and support retransmission to prevent data loss
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with Milesight IoT Cloud and Milesight Development Platform

◆ Specifications

Model	AM307	AM308(L)
Wireless Transmission		
Technology	LoRaWAN®	
Frequency	CN470/RU864/IN865/EU868/US915/AU915/KR920/AS923-1&2&3&4	
Tx Power	16dBm(868MHz)/22dBm(915MHz)/19dBm(470MHz)	
Sensitivity	-137dBm @300bps	
Work Mode	OTAA/ABP Class A	
Sensors		
Temperature		
Operating Principle	Digital CMOSens® technology (MEMS)	
Range	-20°C~60°C	
Accuracy	± 0.2°C	
Resolution	0.1°C	
Humidity		
Operating Principle	Digital CMOSens® technology (MEMS)	
Range	0% ~ 100% RH	
Accuracy	± 2% RH	
Resolution	0.5% RH	
Motion		
Operating Principle	Passive infrared (PIR)	
Detection Range	80 ° Horizontal, 55 ° Vertical, 5m	
Status	Vacant/Occupied	
Light		
Operating Principle	Photodiode	
Range	0-60000 Lux (Determine as 6 levels, 0-5)	
TVOC		
Operating Principle	MOX (MEMS)	
Range ¹	1.00 ~ 5.00 (IAQ Rating)	
Accuracy	±1	
Resolution	0.01	
Barometric Pressure		
Operating Principle	Piezoresistive absolute pressure sensor (MEMS)	
Range	260 - 1260 hPa	

Accuracy	±0.5 hPa	
Resolution	0.1 hPa	
Carbon Dioxide (CO ₂)		
Operating Principle	Nondispersive Infrared (NDIR)	
Range	400 ~ 5000 ppm	
Accuracy	± (30 ppm + 3 % of reading) (0°C~ 50°C, 0% to 85%RH)	
Resolution	1 ppm	
PM2.5 & PM10		
Operating Principle	—	Laser Scattering
Range	—	0 ~ 1000 µg/m ³
Accuracy	—	0~100(±10µg/m ³), 100~1000(±10 %) (-10°C~ 60°C)
Resolution	—	1 µg/m ³
Other Interfaces		
Display	AM307 & AM308: 4.2-inch Black & White E-Ink Screen AM308L: Not Support	
Button	1 × Power Button + 1 × Reset Button	
LED & Buzzer	1 × Traffic Light Status Indicator + 1 × Buzzer	
USB	1 × Type-C Port for Power Supply, Configuration or Console	
Software		
Configuration	1. Mobile App via NFC 2. PC software via NFC or USB Type-C port 3. Downlink	
Advanced Features	Threshold Alarm, Data Storage, Data Retrievability, Data Retransmission	
Physical Characteristics		
Power Supply	1. 4 × 2700 mAh ER14505 Li-SOCl ₂ Replaceable Batteries 2. 5V/1A by Type-C Port	
Battery Life ² (10 min interval, 25°C)	AM307: Around 3 Years	AM308: Over 1 Year AM308L: Around 1.5 Year
Operating Temperature	-20°C - 60°C (E-Ink Screen: 0°C - 40°C)	
Relative Humidity	10% - 90% (non-condensing)	
Ingress Protection	IP30	
Dimension	100.8 × 114 × 22 mm (3.97 × 4.49 × 0.87 in)	
Installation	Wall Mounting via 3M Tape or Screws	

Approvals

Regulatory	CE, FCC, ISED
Environmental	RoHS

Note:

- Reference to IAQ rating guideline (conversion from mg/m³ to ppm by the factor is about 0.5):

IAQ Rating	Air Quality
≤1.99	Very Good
2.00 to 2.99	Good
3.00 to 3.99	Medium (not recommended for exposure > 12 months)
4.00 to 4.99	Poor (not recommended for exposure > 1 months)
≥5.00	Bad (not recommended)

- The battery life is tested under laboratory conditions and for guideline purposes only.

To alert the support team about any issues you are experiencing, please send an email to or create a ticket in our support platform. Please click here: technical@bmetersuk.com

The support team will get back to you as soon as possible.



technical@bmetersuk.com



www.bmetersuk.com



01157 722 506